

8" All-Purpose Passive Subwoofer



CA-SW-8T

Rugged, weather-resistant, and efficient, the CA-SW-8T is a great way to add warmth and body to a wide variety of indoor and outdoor audio installations. A built-in multi-tap transformer with 70-volt (7.5 to 60 watts), 100-volt (15 to 60 watts), and 6-ohm-bypass settings makes it compatible with all types of distributed-sound systems. The subwoofer also has a 150Hz, 12dB/octave low-pass crossover to simplify setup, whether with matching Klipsch CA Series speakers or with other small full-range models. And it requires only modest amplifier power to deliver satisfying output levels.

The CA-SW-8T's 8-inch, long-excursion driver produces extended, powerful bass from its front-ported enclosure. The driver uses a rigid, water-resistant injection-molded graphite (IMG) cone joined to a high-temperature voice coil for consistent, reliable performance.

Available in black or white, the subwoofer's paintable, UV-resistant ABS cabinet has a removable, powder-coated aluminum grille for long, trouble-free service. It is compact and light enough for easy movement, handling, and installation. For wall- or ceiling-mounting, the CA-SW-8T comes with an aluminum C-style bracket that attaches with oversize, positive-lock knobs to threaded stainless steel studs in the sides of the cabinet. A safety retainer on the cabinet allows a secondary attachment point to prevent drop damage.

- High sensitivity and power handling
- Extended, powerful bass
- Internal 60-watt, 70V/100V multi-tap transformer with 6-ohm bypass
- Built-in 150Hz, 12dB/octave low-pass crossover
- Paintable UV-resistant ABS enclosure with rustproof aluminum grille

SPECIFICATIONS

BANDWIDTH ¹	51-135Hz ± 4dB (-10dB @ 42Hz)
POWER HANDLING ²	150W (25V @ 6 ohm input)
MAX CONTINUOUS OUTPUT ³	111dB
SENSITIVITY ⁴	92dB @ 2.83 volts/1 meter
TRANSFORMER TAPS	70V: 60W, 30W, 15W, 7.5W 100V: 60W, 30W, 15W Through Position: 6 ohms
IMPEDANCE	6 ohms nominal (4 ohms min @ 92Hz)
CROSSOVER	12dB/octave low-pass @ 150Hz
COMPONENTS	One 8" IMG cone woofer
INPUT CONNECTORS	5-way binding posts
ENCLOSURE MATERIAL	All-weather ABS plastic
HEIGHT	11.125" (28.26cm)
WIDTH	16.375" (41.53cm)
DEPTH	11.75" (29.88cm)
NET WEIGHT	19 lbs. (8.61kg)
SHIPPING WEIGHT	22 lbs. (10kg)
FINISH	White or Black
MOUNTING	C-Bracket (included); CA Safety Kit (optional)

¹ 3M, half space anechoic

² AES standard, continuous pink noise 50Hz-10Hz, 6dB peaks

³ Calculated at 1M at power handling power input

⁴ Half space anechoic



www.klipsch.com
1-800-KLIPSCH