

6.5" Two-Way In-Wall Loudspeaker



CS-652-W

The direct-radiating CS-652-W takes full advantage of the latest material technologies to deliver performances that are similar to those of our horn-loaded designs. Because it too achieves powerful and dynamic results, the CS-652-W easily blends in with other Klipsch in-wall speakers.

The CS-652-W's copper colored 6.5-inch IMG-cone woofer has a durable rubber surround and a large motor structure for high sensitivity and strong bass output. A 1-inch aluminum-dome tweeter distributes smooth, clear highs over a wide area.

Modestly priced and easy to install, the CS-652-W provides good sound wherever you want it - without making a spectacle of itself. It suits a broad range of applications requiring inconspicuous loudspeakers.

The CS-652-W's rugged ABS frame and powder-coated aluminum grille ensure long, trouble-free operation. And the speaker's 8-ohm impedance is compatible with all amplifiers. The white frame and grille can be painted to match the wall.

- High sensitivity and power handling
- True two-way system for extended frequency range
- Rugged ABS frame and powder-coated steel grille
- Paintable to match wall

SPECIFICATIONS

BANDWIDTH	60Hz-20kHz \pm 3dB
SENSITIVITY	88dB @ 2.83 volts/1 meter
NOMINAL IMPEDANCE	8 ohms compatible
CROSSOVER FREQUENCY	2300Hz
POWER HANDLING	50 watts (200 watts peak)
ENCLOSURE TYPE	Infinite baffle system
DRIVE COMPONENTS	Two-way system using one 1" (2.5cm) aluminum dome tweeter and one 6.5" (16.5cm) IMG cone woofer
WIRE GAUGE ACCOMMODATED	12
WEIGHT	4.5 lbs. (2kg)
HEIGHT	12" (30.5cm)
WIDTH	8.5" (21.6cm)
MOUNTING DEPTH	3.1" (7.9cm)
CUTOUT DIMENSIONS	10.9" (27.7cm) x 7.5" (19cm)
FINISH	White
INSTALLATION KIT	CS-650-W-IK



www.klipsch.com
1-800-KLIPSCH