

## 8" Two-Way In-Ceiling Loudspeaker



# R-3800-C

The R-3800-C in-ceiling loudspeaker delivers superior audio performance while effortlessly integrating into almost any lifestyle. It was designed to deliver all the gusto you'd expect from Klipsch without taking up valuable floor space.

Featuring an 8-inch copper-colored IMG woofer, a 1-inch aluminum tweeter, exclusive Tractrix® Horn technology, as well as a treble contour switch, this affordable and high-performance in-ceiling speaker gives you plenty of bang for your buck.

By incorporating a proprietary two-screw frame design, the R-3800-C is also one of the most easy-to-install products on the market. With this "one trip up the ladder" concept, installers only have to tighten two screws in order to securely mount the loudspeaker into the ceiling.

Available in a white finish, the R-3800-C can be paired with one of Klipsch's new installation kits (sold separately). Each of these revolutionary kit designs allow for increased mounting flexibility and incorporate a mud ring, wire tie and universal metal mesh wing for multi-position placement and a color-coded bracket for easy speaker size identification.

- High sensitivity and power handling, strong bass
- Time saving two-screw mounting method
- Swiveling Tractrix Horn tweeter for clear sound in any location
- Treble attenuation switch

### SPECIFICATIONS

FREQUENCY RESPONSE	48Hz-20kHz ± 3dB
SENSITIVITY	95dB @ 1 watt/1 meter
NOMINAL IMPEDANCE	8 ohms
CROSSOVER FREQUENCY	2600Hz
POWER HANDLING	50 watts (200 watts peak)
ENCLOSURE MATERIAL/ TYPE	ABS, Infinite baffle, front flush with ceiling
DRIVE COMPONENTS	Two-way system using one 1" (2.54cm) Aluminum dome compression tweeter with a swiveling 100° Asymmetrical Tractrix® Horn and one 8" (20.32cm) IMG woofer
WIRE GAUGE ACCOMMODATED	12
WEIGHT	7.9 lbs. (3.6kg)
DIAMETER	11" (27.94cm)
MOUNTING DEPTH	4.5" (11.43cm)
CUTOUT DIMENSIONS	9.75" (24.77cm)
FINISH	White
INSTALLATION KIT	IK-800-C (sold separately)

www.klipsch.com  
1-800-KLIPSCH

