

## 8" Two-Way In-Wall Loudspeaker



# R-3800-W

Discrete but not understated, the high-performance and installer-friendly R-3800-W in-wall loudspeaker delivers all the gusto you'd expect from Klipsch.

Featuring an 8-inch copper-colored IMG woofer, a 1-inch aluminum tweeter, exclusive Tractrix® Horn technology, as well as a treble contour switch, this dynamic in-wall speaker gives you plenty of bang for your buck and brings high-quality entertainment into your home without taking up valuable floor space.

Available in a white finish, the R-3800-W can be paired with one of Klipsch's new installation kits (sold separately). Each of these revolutionary kit designs allow for increased mounting flexibility and incorporate a mud ring, wire tie and universal metal mesh wing for multi-position placement and a color-coded bracket for easy speaker size identification.

- High sensitivity and power handling
- Pivoting Tractrix Horn compression driver tweeter for clear sound in any location
- Treble attenuation switch and IR receiver knock out
- Single piece grille frame and rustproof aluminum grille

### SPECIFICATIONS

FREQUENCY RESPONSE	46Hz-20kHz ± 3dB
SENSITIVITY	93dB @ 1 watt/1 meter
NOMINAL IMPEDANCE	8 ohms
CROSSOVER FREQUENCY	2200Hz
POWER HANDLING	50 watts (200 watts peak)
ENCLOSURE MATERIAL/TYPE	ABS/ Infinite baffle, front flush with wall
DRIVE COMPONENTS	Two-way system using one 1" (2.54cm) Aluminum dome compression tweeter with a 6" (15.24cm) square 90° x 60° pivoting Tractrix® Horn and one 8" (20.32cm) IMG woofer
WIRE GAUGE ACCOMMODATED	12
WEIGHT	7.9 lbs. (3.6kg)
HEIGHT	16.1" (40.89cm)
WIDTH	10.6" (26.92cm)
MOUNTING DEPTH	3.75" (9.5cm)
CUTOUT DIMENSIONS	14.75" (37.47cm) x 9.25" (23.50cm)
FINISH	White
INSTALLATION KIT	IK-800-W (sold separately)

www.klipsch.com  
1-800-KLIPSCH

