

RC-500



CENTER SPEAKER WITH ELEGANT FINISH

Black ash woodgrain vinyl

TRACTRIX® HORN

Proprietary technology provides a unique combination of precision, clarity and effortless power

TITANIUM DIAPHRAGM COMPRESSION DRIVER (TWEETER)

Produces the most detailed high frequencies

TAPERED ARRAY TECHNOLOGY

Eliminates acoustic interference between woofers for improved clarity

CERAMETALLIC™ CONE WOOFERS

Ensure tight musical bass

DUAL FRONT-FIRING PORTS

Grant placement flexibility without sacrificing consistent bass performance

KLIPSCH BELIEVES FOUR PRINCIPLES TO BE THE FOUNDATION FOR GREAT SOUND:

- **HIGH EFFICIENCY:** Every Klipsch speaker is horn-loaded because the horn shape is perfect for accurate and dynamic sound transmission. Greater efficiency means lower distortion which means maximum realism.
- **DYNAMIC RANGE:** Klipsch horn technology reproduces the softest sounds with remarkable clarity and detail and the loudest sounds with no harshness or distortion. That's what's known as the best of both worlds.
- **CONTROLLED DIRECTIVITY:** Unique Klipsch horn technology means speakers that more accurately direct sound. The result is a more lifelike soundstage and way more "Whoa - Did you hear that?"
- **FLAT FREQUENCY RESPONSE:** We believe in delivering exactly the sound artists intend. Hence, Klipsch's stunningly accurate speakers - with no unnatural highs, mids or lows.

SPECIFICATIONS	RC-500
Frequency Response	67Hz-23KHz ± 3dB
Power Handling	125W RMS / 500W Peak
Sensitivity	96dB @ 2.83V / 1m
Nominal Impedance	8 ohms compatible
High Frequency Drivers	1" (2.54cm) Titanium diaphragm compression driver mated to 90° x 60° square Tractrix® Horn
High Frequency Crossover	14000Hz, 1600Hz
Low Frequency Drivers	Dual 5.25" (13.3cm) Cerametallic™ cone woofers
Inputs	Single binding posts
Enclosure Type	Bass-reflex via dual front-firing ports
Height	6.5" (16.6cm)
Width	20.5" (52.1cm)
Depth	10.5" (26.6cm) with grille
Mounting	Uptilt and Downtilt feet
Weight	22.1lbs (10kg)
Finish	Black Ash woodgrain vinyl
Built From	2012