

RC-42 II



CENTER SPEAKER WITH ELEGANT FINISH

Black ash woodgrain vinyl

TRACTRIX® HORN

Proprietary technology provides a unique combination of precision, clarity and effortless power

TITANIUM DIAPHRAGM COMPRESSION DRIVER (TWEETER)

Produces the most detailed high frequencies

LINEAR TRAVEL SUSPENSION

Minimizes distortion

CERAMETALLIC™ CONE WOOFERS

Ensure tight musical bass

DUAL FRONT-FIRING PORTS

Grant placement flexibility without sacrificing consistent bass performance

KLIPSCH BELIEVES FOUR PRINCIPLES TO BE THE FOUNDATION FOR GREAT SOUND:

- **HIGH EFFICIENCY:** Every Klipsch speaker is horn-loaded because the horn shape is perfect for accurate and dynamic sound transmission. Greater efficiency means lower distortion which means maximum realism.
- **DYNAMIC RANGE:** Klipsch horn technology reproduces the softest sounds with remarkable clarity and detail and the loudest sounds with no harshness or distortion. That's what's known as the best of both worlds.
- **CONTROLLED DIRECTIVITY:** Unique Klipsch horn technology means speakers that more accurately direct sound. The result is a more lifelike soundstage and way more "Whoa - Did you hear that?"
- **FLAT FREQUENCY RESPONSE:** We believe in delivering exactly the sound artists intend. Hence, Klipsch's stunningly accurate speakers - with no unnatural highs, mids or lows.

SPECIFICATIONS	RC-42 II
Frequency Response	88Hz-24KHz ± 3dB
Power Handling	75W RMS / 300W Peak
Sensitivity	95dB @ 2.83V / 1m
Nominal Impedance	8 ohms compatible
High Frequency Drivers	1" (2.54cm) Titanium diaphragm compression driver mated to 90° x 60° square Tractrix® Horn
High Frequency Crossover	1700Hz
Low Frequency Drivers	Dual 4" (10.2cm) Cerametallic™ cone woofers
Inputs	Single binding posts
Enclosure Type	Bass-reflex via dual front-firing ports
Height	5.4" (13.7cm)
Width	16" (40.7cm)
Depth	8.9" (22.7cm) with grille
Mounting	Uptilt and Downtilt feet
Weight	12.6lbs (5.7kg)
Finish	Black Ash woodgrain vinyl
Built From	2010