



Dual 8" Two-Way Floorstanding Loudspeaker

RF-35

Extended low-frequency response, extraordinary efficiency, and very high output capability make the RF-35 a true performance and value leader. Requiring less than a quarter the amplifier power of conventional speakers, it conveys the full emotional impact of whatever signal it is fed, without strain or limitation. Whether standing alone in a stereo music system or fronting a sophisticated home theater, the RF-35 brings the experience home with maximum intensity. And because it is perfectly matched cosmetically and sonically to other Klipsch Reference Series loudspeakers, it allows flexibility in system configuration.

The RF-35 uses a 1-inch titanium dome compression driver tweeter for the high frequencies, loaded by a 6-inch square 90° x 60° Tractrix® Horn molded into the front of the enclosure. The horn raises the driver's efficiency and controls its radiation pattern to minimize detail-blurring reflections from walls, floor, and ceiling. Dual Cerametallic™ cone woofers with rigid, low-resonance cast-polymer frames generate powerful, dynamic bass. All drivers are magnetically shielded to prevent interference with direct-view television sets.

Amplifier connections are via two pairs of binding posts, which are strapped together for normal wiring. Removing the straps allows the speaker to be bi-wired. Magnetic posts hold the RF-35's low-diffraction grille securely in place, and the outrigger feet can be fitted with adjustable-height rubber pads or spikes. The rear-ported cabinet is available in a Black Ash or Light Cherry woodgrain vinyl finish.

- Extremely high sensitivity and power-handling
- Tractrix Horn titanium dome compression driver tweeter for clean, detailed highs
- Cerametallic cone woofers with cast-polymer frames
- Bi-wire compatible inputs
- Magnetically shielded to prevent video interference

SPECIFICATIONS

BANDWIDTH	37Hz-20kHz ± 3dB
SENSITIVITY	98dB @ 2.83 volts/1 meter
NOMINAL IMPEDANCE	8 ohms compatible
CROSSOVER FREQUENCY	2600Hz
POWER HANDLING	125 watts (500 watts peak)
ENCLOSURE TYPE	Bass-reflex via rear-firing port
DRIVE COMPONENTS	Two way system using one 1" (2.5cm) magnetically shielded, titanium dome compression driver with an integral 6" (15.2cm) square 90° x 60° Tractrix Horn and two 8" (20.3cm) magnetically shielded, Cerametallic cone woofers
WEIGHT	54 lbs. (24.5kg)
HEIGHT	40.9" (103.9cm) w/feet, 40" w/o feet
WIDTH	9.3" (23.6cm)
DEPTH	14.8" (37.6cm)
FINISH	Black Ash or Light Cherry Woodgrain Vinyl



www.klipsch.com
1-800-KLIPSCH