

10" Powered Subwoofer



RPW-10

An ideal combination of technology, performance and design, the Reference Series RPW-10 subwoofer brings a deep, tuneful bottom end to home theater and two-channel music systems.

As the most affordable subwoofer in the Reference Series line, the RPW-10 delivers room-shaking bass courtesy of a 10-inch fiber composite front-firing woofer and a 200-watt RMS amplifier.

Featuring traditional volume, crossover and phase controls, the RPW-10's front-firing slot port makes installation into custom cabinetry a breeze. Available in a black matte vinyl finish, this powerhouse brings a new level of performance to the value-priced subwoofer category.

SPECIFICATIONS

ENCLOSURE TYPE	Bass-reflex via front-firing slot port
ACTIVE DRIVERS	10" (25.4cm) Fiber-composite cone, front-firing woofer
AMPLIFIER TYPE	BASH® Digital hybrid
AMPLIFIER POWER	FTC Rated Power: 200 watts continuous @ <2% THD / Dynamic Power*: 420 watts
BANDWIDTH	35-120Hz ± -3dB
MAXIMUM OUTPUT	110dB @ 30Hz 1/8 space, 1m
CONTROLS	Volume, Lowpass, Phase, Auto Power
INPUTS	L/R Line-level RCA jacks, L/R High-level speaker binding posts
OUTPUTS	L/R High-level speaker binding posts (passthru)
FINISHES	Black matte vinyl
WEIGHT	31 lbs. (14.1kg)
HEIGHT	15.75" (40cm)
WIDTH	11.5" (29.2cm)
DEPTH	17.75" (45.1cm)
VOLTAGE	110/120 VAC 60Hz
EXPORT VERSION	220 VAC 50/60Hz

*Dynamic power indicates the actual power this amplifier will deliver to the woofer under normal operating conditions. While the FTC power rating indicates power available on a continuous, long-term basis, subwoofers do not rely on that type of power. Instead, the amplifier is called upon to deliver large, short-term peaks of power to be able to support the wide dynamics required by today's digital music and movie formats. In addition to the required FTC power rating, we've provided the dynamic power rating as a better indication of the product's true performance.



www.klipsch.com
1-800-KLIPSCH