

4" Two-Way Surround Loudspeaker



RS-10

Part of the new entry-level Reference 10 family, the RS-10 surround loudspeaker offers the same advanced technology and world-class materials as the Reference III surrounds but from a smaller enclosure and at a lower price point.

The RS-10 delivers precise sonic detail through the careful positioning of two Tractrix® Horn loaded titanium-dome tweeters and one 4-inch woofer. By aligning the two horns at 90° with respect to each other, along with the front-firing woofer, the RS-10 smoothly covers a 180-degree horizontal arc, allowing maximum placement flexibility. This unique Wide Dispersion Surround Technology™ delivers a new dimension of reality and convenience, and produces a smooth, seamless broad distribution of sound, which is the perfect vehicle for every surround format.

The woofer on the RS-10 still features Klipsch's distinctive, copper-colored Cerametallic™ material. Made with an anodized aluminum, this cone is strong with low mass. The anodizing process converts its inner and outer surfaces to ceramic. The outcome is a rigid cone with superb damping characteristics that will not flex or resonate at frequencies within the woofer's operating range.

As in all Reference Series speakers, the RS-10 crossover network is constructed using extremely high-quality components including top-of-the-line internal wiring, polyester film-type capacitors and an air-core inductor to ensure signal purity and proper driver integration.

The RS-10 comes with a back-panel keyhole for on-wall mounting and a threaded insert for attachment to popular adjustable wall and ceiling brackets. Available in a black ash vinyl finish, the RS-10 features an elegant fit and finish.

- Back-panel keyhole and threaded insert for wall or ceiling mounting
- WDST design for superior surround envelopment and effect localization
- Dual Tractrix Horn titanium dome compression driver tweeters
- Cerametallic cone woofer
- High sensitivity and power handling

SPECIFICATIONS

BANDWIDTH	82Hz-20kHz ± 3dB
SENSITIVITY	91dB @ 2.83 volts/1 meter
IMPEDANCE	8 ohms compatible
CROSSOVER FREQUENCY	2000Hz
POWER HANDLING	50 watts (200 watts peak)
ENCLOSURE TYPE	Sealed
DRIVE COMPONENTS	Two-way system using two 1" (2.5cm) titanium dome compression drivers with 4" (10.2cm) square 90° x 60° Tractrix Horns and one 4" (10.2cm) Cerametallic cone woofer
WEIGHT	5 lbs. (2.3kg)
HEIGHT	6.8" (12.3 cm)
WIDTH	12.7" (32.3cm)
DEPTH	5.8" (14.7cm)
FINISH	Black Ash vinyl
MOUNTING	Keyhole mount with threaded insert

*All dimensions include grille and binding posts



www.klipsch.com
1-800-KLIPSCH

All specifications are subject to change without notice. ©2004