

Dual 10" Powered Subwoofer



RSW-10d

Even though it's the smallest subwoofer in the Reference Series line, the RSW-10d Digitally Controlled Subwoofer (DCS™) still hurls out enough seismic power to shake the foundation. With its high-end materials and superb design, this class-leading performer perfectly anchors a home theater or two-channel stereo music system.

The RSW-10d gets its hard-hitting intensity courtesy of dual ultra high-output 10-inch Cerametallic™ drivers (one front-firing passive radiator, one rear-firing woofer) and a 500-watt RMS amplifier.

For quick and easy adjustment of all functions, the RSW-10d features the DCS digital user-interface that includes three equalization modes (flat, depth and punch) and three user-adjustable presets (music, movie and night) to create specific listening preferences.

Available in a cherry or black woodgrain vinyl finish, the RSW-10d also comes with an IR sensor for operation from any learning remote or control system.

SPECIFICATIONS

ENCLOSURE TYPE	Bass-reflex via front-firing passive radiator
ACTIVE DRIVERS	Ultra-high-excursion 10" (25.4cm) Cerametallic™ cone, rear-firing woofer
PASSIVE DRIVERS	Ultra-high-excursion 10" (25.4cm) Cerametallic™ cone, front-firing passive radiator
AMPLIFIER TYPE	BASH® Digital hybrid
AMPLIFIER POWER	FTC Rated Power: 500 watts continuous @ <2% THD / Dynamic Power*: 1200 watts
BANDWIDTH	24-120Hz ± -3dB
MAXIMUM OUTPUT	114dB @ 30Hz 1/8 space, 1m
CONTROLS	DCS control and feature set w/ 3 system presets
INPUTS	L/R Line-level RCA jacks
OUTPUTS	None
FINISHES	Cherry or Black Ash wood grain vinyl
WEIGHT	45 lbs. (20.4kg)
HEIGHT	13.75" (34.9cm)
WIDTH	12.75" (32.4cm)
DEPTH	17.5" (44.5cm)
VOLTAGE	110/120 VAC 60Hz
EXPORT VERSION	220 VAC 50/60Hz

*Dynamic power indicates the actual power this amplifier will deliver to the woofer under normal operating conditions. While the FTC power rating indicates power available on a continuous, long-term basis, subwoofers do not rely on that type of power. Instead, the amplifier is called upon to deliver large, short-term peaks of power to be able to support the wide dynamics required by today's digital music and movie formats. In addition to the required FTC power rating, we've provided the dynamic power rating as a better indication of the product's true performance.



www.klipsch.com
1-800-KLIPSCH