

Quad 5.25" Two-Way Floorstanding Loudspeaker



RVX-54

As plasma and LCD television sales continue to soar, Klipsch is introducing a true, high-performance audio solution that will accommodate this growing segment. With similar flatness and style, the Klipsch Reference Series RVX-54 floorstander represents the ultimate in performance, style and functionality for these hot-selling televisions.

The RVX-54 has a single-piece aluminum extrusion enclosure. It employs four active 5.25-inch aluminum woofers and uses a 1-inch titanium-dome compression drivers mated to a round Tractrix® Horn for maximum clarity and efficiency.

Available in the same black or silver finish as the Klipsch Reference Satellites, the RVX-54 can be combined with these compact speakers to create complete systems. For example, consumers can create a 5.1-channel surround sound system using a pair of RVX-54s, a pair of Reference Satellite RSX-4s for surrounds, a RVX-42 for a center channel and a Reference Series RW-12 subwoofer.

The RVX-54 is packaged and sold individually for mix-and-match simplicity.

- Very high sensitivity
- MicroTractrix Horn tweeter for clean, detailed highs
- Integrates well with all Klipsch powered subwoofers
- Magnetically shielded drivers to prevent video interference
- Bi-Wire compatible inputs

SPECIFICATIONS

BANDWIDTH	75Hz-20kHz ± 3dB
SENSITIVITY	98dB @ 2.83 volts/1 meter
NOMINAL IMPEDANCE	8 ohms compatible
CROSSOVER FREQUENCY	2300Hz
POWER HANDLING	150 watts (600 watts peak)
ENCLOSURE TYPE	Bass-reflex via rear-firing port
DRIVE COMPONENTS	Two way multiple tapered array system using one 1" (2.5cm) magnetically shielded, titanium dome compression driver tweeter with an integral round 90° MicroTractrix Horn and four 5.25" (13.3cm) magnetically shielded, Cerametallic cone woofers
WEIGHT	40 lbs. (18.1kg)
HEIGHT	49.3" (125.1cm)
WIDTH	7" (17.8cm)/11" (27.9cm) at the base
DEPTH	6.5" (16.5cm)/11" (27.9cm) at the base
FINISH	Black or Silver



www.klipsch.com
1-800-KLIPSCH