

5.25" Two-Way In-Ceiling Loudspeaker



SCR-1

Klipsch Custom Series architectural speakers are carefully engineered using the latest technology to deliver superb performance and unparalleled value. Smallest in the line, the versatile, easy-to-install SCR-1 is an excellent choice for distributed-music systems and other applications requiring unobtrusive, high-quality loudspeakers. SCR-1s can work well as surround speakers in home theater systems, for example. And their sound blends well with that of other Klipsch speakers, whether built-in or freestanding.

Manufactured on a rigid, low-resonance cast-polymer frame, the SCR-1 delivers remarkably clean, rich bass from its 5.25-inch IMG-cone woofer. And its coaxially mounted 1-inch aluminum dome compression driver tweeter is mated to a 100° asymmetrical Klipsch Tractrix® Horn that can be swivled to focus sound where needed, which is a great advantage when the speaker must be mounted in a less-than-ideal location. A tweeter attenuation switch conveniently mounted behind the grille gives an added measure of control in tailoring the speaker's output to the acoustics of its environment.

The SCR-1's white frame and rustproof, powder-coated aluminum grille can be painted to match the ceiling. High-quality components and superior construction assure long, reliable service. And the speaker's 8-ohm impedance is compatible with all amplifiers.

- High sensitivity and power handling
- Durable cast-polymer frame with shallow 4.5-inch mounting depth
- Swiveling Tractrix Horn compression driver tweeter for clear sound in any location
- Adjustable treble output
- Frame and rustproof aluminum grille paintable to match ceiling

SPECIFICATIONS

| | |
|-------------------------|---|
| BANDWIDTH | 75Hz-20kHz ± 3dB |
| SENSITIVITY | 92dB @ 2.83 volts/1 meter |
| NOMINAL IMPEDANCE | 8 ohms compatible |
| CROSSOVER FREQUENCY | 2300Hz |
| POWER HANDLING | 50 watts (200 watts peak) |
| ENCLOSURE TYPE | Infinite baffle system |
| DRIVE COMPONENTS | Two-way system using one 1" (2.5cm) aluminum dome compression driver tweeter with a swiveling 100° symmetrical Tractrix Horn and one 5.25" (13.3cm) IMG cone woofer |
| WIRE GAUGE ACCOMMODATED | 12 |
| WEIGHT | 3 lbs. (1.4kg) |
| DIAMETER | 8" (20.3cm) |
| MOUNTING DEPTH | 4.5" (11.4cm) |
| CUTOUT DIMENSIONS | 7" (17.8cm) |
| FINISH | White |
| INSTALLATION KIT | R-525-IK |



www.klipsch.com
1-800-KLIPSCH