

6.5" Two-Way In-Ceiling Loudspeaker



SCR-2

Klipsch Custom Series architectural speakers are carefully engineered using the latest materials and technology to deliver superb performance and unparalleled value. Mid-sized among the in-ceiling models, the versatile, easy-to-install SCR-2 is an excellent choice for distributed-music systems and other applications requiring unobtrusive, high-quality loudspeakers. SCR-2s can work well as surround speakers in home theater systems, for example. In addition, their sound blends well with that of other Klipsch speakers, whether built-in or freestanding.

Constructed on a rigid, low-resonance cast-polymer frame, the SCR-2 delivers notably robust bass from its 6.5-inch IMG-cone woofer. In this respect alone, it is an obvious step up from everyday utility ceiling speakers. Its coaxially mounted 1-inch aluminum-dome compression driver tweeter is mated to a 100° asymmetrical Klipsch Tractrix® Horn that can be swiveled to focus sound where needed — a significant advantage when circumstances dictate a less-than-ideal install location. A tweeter attenuation switch conveniently placed behind the grille provides another tool for tailoring the speaker's output to the acoustics of its environment.

The SCR-2's white frame and rustproof, powder-coated aluminum grille can be painted to match the ceiling. High-quality components and superior construction assure long, reliable service. And the speaker's 8-ohm impedance is compatible with all amplifiers.

- High sensitivity and power handling
- Durable cast-polymer frame with shallow 4.5" mounting depth
- Swiveling Tractrix Horn compression driver tweeter for clear sound in any location
- Adjustable treble output
- Frame and rustproof aluminum grille paintable to match ceiling

SPECIFICATIONS

BANDWIDTH	50Hz-20kHz ± 3dB
SENSITIVITY	92dB @ 2.83 volts/1 meter
NOMINAL IMPEDANCE	8 ohms compatible
CROSSOVER FREQUENCY	2100Hz
POWER HANDLING	50 watts (200 watts peak)
ENCLOSURE TYPE	Infinite baffle system
DRIVE COMPONENTS	Two-way system using one 1" (2.5cm) aluminum dome compression driver tweeter with a swiveling 100° symmetrical Tractrix Horn and one 6.5" (16.5cm) IMG cone woofer
WIRE GAUGE ACCOMMODATED	12
WEIGHT	4 lbs. (1.8kg)
DIAMETER	9.3" (23.6cm)
MOUNTING DEPTH	4.5" (11.4cm)
CUTOUT DIMENSIONS	8.3" (21.1cm)
FINISH	White
INSTALLATION KIT	R-650-IK



www.klipsch.com
1-800-KLIPSCH

All specifications are subject to change without notice. ©2004