

8" Two-Way In-Ceiling Loudspeaker



SCR-3

Klipsch Custom Series architectural speakers are engineered using the latest materials and technology to deliver superior performance and value. The versatile, easy-to-install SCR-3 is an excellent choice for distributed-music systems and other applications requiring unobtrusive, high-quality loudspeakers, especially where good low-frequency output is desired. SCR-3s can work well as surround speakers in home theater systems, for example. In addition, their sound blends well with that of other Klipsch speakers of all varieties, from smaller in-ceiling speakers like the SCR-1 to big floorstanders.

Indeed, with its rigid, low-resonance cast-polymer frame and 8-inch injection-molded graphite cone, the SCR-3's woofer delivers bass so rich and full that people often think it must be coming from a big freestanding speaker. The overall quality of the sound is well beyond what ordinary ceiling speakers have conditioned listeners to expect. Mounted coaxial to the woofer is a 1-inch aluminum-dome compression driver tweeter with a 100° asymmetrical Klipsch Tractrix® Horn that can be swiveled to focus sound where needed — a significant benefit when circumstances dictate less-than-ideal speaker positioning. A tweeter attenuation switch located conveniently behind the grille also helps tailor the SCR-3's output to the acoustics of its environment.

The white frame and rustproof, powder-coated aluminum grille can be painted to match the ceiling. High-quality components and rugged construction assure long, reliable service. And the speaker's 8-ohm impedance is compatible with all amplifiers.

- High sensitivity and power handling, strong bass
- Durable cast-polymer frame with shallow 5" mounting depth
- Swiveling Tractrix Horn tweeter for clear sound in any location
- Adjustable treble output
- Frame and rustproof aluminum grille paintable to match ceiling

SPECIFICATIONS

BANDWIDTH	39Hz-20kHz ± 3dB
SENSITIVITY	94dB @ 2.83 volts/1 meter
NOMINAL IMPEDANCE	8 ohms compatible
CROSSOVER FREQUENCY	2300Hz
POWER HANDLING	50 watts (200 watts peak)
ENCLOSURE TYPE	Infinite baffle system
DRIVE COMPONENTS	Two-way system using one 1" (2.5cm) aluminum dome compression driver tweeter with a swiveling 100° symmetrical Tractrix Horn and one 8" (20.3cm) IMG cone woofer
WIRE GAUGE ACCOMMODATED	12
WEIGHT	5 lbs. (2.3kg)
DIAMETER	10.8" (27.4cm)
MOUNTING DEPTH	5" (12.7cm)
CUTOUT DIMENSIONS	9.8" (24.9cm)
FINISH	White
INSTALLATION KIT	R-800-IK



www.klipsch.com
1-800-KLIPSCH

All specifications are subject to change without notice. ©2004