

5.25" Two-Way In-Wall Loudspeaker



SCW-1

Klipsch Custom Series architectural speakers are carefully engineered using the latest technology to deliver superb performance and unparalleled value. Small and easy-to-install, the SCW-1 is a great solution anywhere indoors that concealed speakers are needed. This includes everything from high-quality distributed-music systems in commercial spaces to stealth home theater installations. In fact, with subwoofer support, SCW-1s can be used for every channel in a home-theater system with excellent results. And because they share so many design elements with our freestanding speakers, their sound blends perfectly in mixed systems, giving you maximum flexibility.

Manufactured on a rigid, low-resonance cast-polymer frame, the SCW-1 delivers remarkably clean, rich bass from its 5.25-inch IMG-cone woofer. A 1-inch aluminum-dome compression driver tweeter is mated to a 5-inch square 90° x 60° Klipsch Tractrix® Horn that increases efficiency and controls the sound radiation pattern for improved clarity. A tweeter attenuation switch conveniently placed behind the grille helps tailor the speaker's output to the acoustics of its environment, and an IR punchout accepts standard infrared receivers.

The SCW-1's white frame and rustproof, powder-coated aluminum grille can be painted to match the wall. High-quality components and superior construction assure long, reliable service. And the speaker's 8-ohm impedance is compatible with all amplifiers.

- High sensitivity and power handling
- Durable cast-polymer frame with shallow 3.1" mounting depth
- Tractrix Horn compression driver tweeter for clean, clear highs
- Tweeter attenuation switch and IR receiver punchout
- Frame and rustproof aluminum grille paintable to match wall

SPECIFICATIONS

BANDWIDTH	65Hz-20kHz ± 3dB
SENSITIVITY	92dB @ 2.83 volts/1 meter
NOMINAL IMPEDANCE	8 ohms compatible
CROSSOVER FREQUENCY	2100Hz
POWER HANDLING	50 watts (200 watts peak)
ENCLOSURE TYPE	Infinite baffle system
DRIVE COMPONENTS	Two-way system using one 1" (2.5cm) aluminum dome compression driver tweeter with a 90° x 60° Tractrix Horn and one 5.25" (13.3cm) IMG cone woofer
WIRE GAUGE ACCOMMODATED	12
WEIGHT	4 lbs. (1.8kg)
HEIGHT	11.7" (29.7cm)
WIDTH	7.8" (19.8cm)
MOUNTING DEPTH	3.1" (7.9cm)
CUTOUT DIMENSIONS	10.8" (27.4cm) x 6.8" (17.3cm)
FINISH	White
INSTALLATION KIT	W-525-IK



www.klipsch.com
1-800-KLIPSCH