

## 8" Two-Way In-Wall Loudspeaker



# SCW-3

Klipsch Custom Series architectural speakers are engineered using the latest materials and technology to deliver superior performance and value. The versatile, easy-to-install SCW-3 is an excellent choice for distributed-music systems and other applications requiring unobtrusive, high-quality loudspeakers, especially where high output and extended bass are desired. SCW-3s work well in stealth home theater installations, for example, especially if the system includes a subwoofer. And their sound blends well with that of other Klipsch speakers of all varieties, from smaller in-walls and in-ceilings, such as the SCW-I and SCR-I, to big floorstanders.

With its rigid, low-resonance cast-polymer frame and 8-inch injection-molded graphite cone, the SCW-3's woofer generates rich, full bass that actually compares well in both quantity and quality to that from full-size freestanding loudspeakers. The 1-inch aluminum-dome compression driver tweeter with a 6-inch square 90° x 60° Klipsch Tractrix® Horn can be pivoted to focus sound where needed — a significant advantage when circumstances dictate less-than-ideal speaker positioning. A tweeter attenuation switch located conveniently behind the grille also helps tailor the SCW-3 output to the acoustics of its environment.

The white frame and rustproof, powder-coated aluminum grille can be painted to match the wall; an IR punchout accepts standard infrared receivers. High-quality components and rugged construction assure long, reliable service. And the speaker's 8-ohm impedance is compatible with all amplifiers.

- High sensitivity and power handling
- Durable cast-polymer frame with shallow 3.75" mounting depth
- Pivoting Tractrix Horn compression driver tweeter for clear sound in any location
- Tweeter attenuation switch and IR receiver punchout
- Frame and rustproof aluminum grille paintable to match wall

## SPECIFICATIONS

BANDWIDTH	38Hz-20kHz ± 3dB
SENSITIVITY	93dB @ 2.83 volts/1 meter
NOMINAL IMPEDANCE	8 ohms compatible
CROSSOVER FREQUENCY	2400Hz
POWER HANDLING	50 watts (200 watts peak)
ENCLOSURE TYPE	Infinite baffle system
DRIVE COMPONENTS	Two-way system using one 1" (2.5cm) aluminum dome compression driver tweeter with a pivoting 90° x 60° Tractrix Horn and one 8" (20.3cm) IMG cone woofer
WIRE GAUGE ACCOMMODATED	12
WEIGHT	6 lbs. (2.7kg)
HEIGHT	15.8" (40.1 cm)
WIDTH	10.2" (26cm)
MOUNTING DEPTH	3.75" (9.5cm)
CUTOUT DIMENSIONS	14.8" (37.6cm) x 9.3" (23.6cm)
FINISH	White
INSTALLATION KIT	W-800-IK



www.klipsch.com  
1-800-KLIPSCH