

SW-110



Compact subwoofer with stylish finish

Black matte vinyl complements impeccable design

Highly damped, non-resonant woven fiberglass driver

Produces tight musical bass

BASH® Digital Hybrid Amplifier

Efficiently produces reliable, high-powered sound

Front slot ports

Provide deep bass and installation and placement flexibility

Line and high level inputs

Ensure compatibility with old and new receivers

1-watt standby mode

Energy-saving feature

Powerful and efficient bass extension is at the heart of every Klipsch subwoofer. Crafted to effortlessly integrate and perform with any brand or speaker model, our new compact subwoofer models are here to produce the mind-blowing sound Klipsch is known for in any home.

KLIPSCH BELIEVES THREE PRINCIPLES TO BE THE FOUNDATION FOR GREAT BASS:

High Efficiency/Low Distortion: Efficient bass reflex enclosure designs with high output drivers. Ports are designed for linear air flow and low noise. High output bass extension with less amplifier power ensures effortless performance.

High Dynamic Range: The ability to play loud without dynamic compression keeps the impact and realism that imitates life. Powerful music and movie effects are delivered with authenticity. Amplifiers are designed to deliver peak power that never restricts maximum acoustic output. Given the designs are more efficient than competitors', Klipsch subwoofers play louder (dynamics) with less amplifier power.

Extended Flat Bass Response: Bass reaches deep into the lowest octave with natural, smooth extended response, ensuring musical non-fatiguing sound as well as authoritative power.

SPECIFICATIONS	SW-110
Frequency Response	28Hz-120Hz ± 3dB
Maximum Acoustic Output	113dB @ 30Hz 1/8 space, 1m
Amplifier Type	BASH Digital Hybrid
Amplifier Power	FTC Rated Power: 200 watts continuous @ <2% THD / Dynamic Power*: 450 watts
Driver Components	10" (25.4cm) Active non-resonant Woven Fiberglass driver
Enclosure Type	Bass-reflex via front-firing slot port
Inputs	L/R Line-level RCA jacks, L/R High-level speaker binding posts, WA port
Outputs	None
Height	14" (35.6cm)
Width	12.5" (31.8cm)
Depth	17" (43.2cm)
Weight	35lbs (15.9kg)
Finish	Black pica
Voltage	100-120V / 220-240V~50/60Hz 2A (Auto-voltage switching) with 1 Watt standby
Export Version	NA, EU, CCC
Built From	2010