

SW-311



Compact subwoofer with stylish finish

Pristine black satin finish complements impeccable design

Digital Control System™ (DCS)

Offers easy-to-access front controls to adjust preferences to your suit your listening needs

ARC II

Automatically customizes optimal bass performance for any room

Highly damped, non-resonant woven fiberglass driver

Produces tight musical bass

BASH® Digital Hybrid Amplifier

Efficiently produces reliable, high-powered sound

4-layer copper voice coil on aluminum former

Provides enhanced low-end output

1-watt standby mode

Energy-saving feature

Powerful and efficient bass extension is at the heart of every Klipsch subwoofer. Crafted to effortlessly integrate and perform with any brand or speaker model, our new compact subwoofer models are here to produce the mind-blowing sound Klipsch is known for in any home.

KLIPSCH BELIEVES THREE PRINCIPLES TO BE THE FOUNDATION FOR GREAT BASS:

High Efficiency/Low Distortion: Efficient bass reflex enclosure designs with high output drivers. Ports are designed for linear air flow and low noise. High output bass extension with less amplifier power ensures effortless performance.

High Dynamic Range: The ability to play loud without dynamic compression keeps the impact and realism that imitates life. Powerful music and movie effects are delivered with authenticity. Amplifiers are designed to deliver peak power that never restricts maximum acoustic output. Given the designs are more efficient than competitors', Klipsch subwoofers play louder (dynamics) with less amplifier power.

Extended Flat Bass Response: Bass reaches deep into the lowest octave with natural, smooth extended response, ensuring musical non-fatiguing sound as well as authoritative power.

SPECIFICATIONS	SW-311
Frequency Response	22Hz-120Hz ± 3dB
Maximum Acoustic Output	118dB @ 30Hz 1/8 space, 1m
Amplifier Type	BASH Digital Hybrid
Amplifier Power	FTC Rated Power: 500 watts continuous @ <2% THD / Dynamic Power*: 1200 watts
Driver Components	10" (25.4cm) Active / Dual 10" Passive non-resonant Woven Fiberglass drivers
Enclosure Type	Bass-reflex via dual side-firing passive radiators
Inputs	L/R Line-level RCA jacks, USB, 12V Trigger, MIC, WA port
Outputs	Line-level RCA jack
Height	13" (33cm)
Width	13" (33cm)
Depth	14" (35.6cm)
Weight	37lbs (16.8kg)
Features	DCS control and feature set w/ 5 system presets and Adaptive Room Correction II with 12 active filters
Finish	Black satin
Voltage	100-120V / 220-240V~50/60Hz 5A (Auto-voltage switching) with 1 Watt standby
Export Version	NA, EU
Built From	2010