



XL-23 LCR

Engineered for pure, dynamic listening, the XL-23 utilizes a premium titanium diaphragm compression driver and dual high-output fiberglass cone woofers.

But what puts this flat-panel speaker above the rest is an all-new patent-pending Tractrix[®] horn-loaded tweeter with XT[™] technology. For over 60 years, horns have been the driving force behind our stunningly precise sound, and this latest design moves us farther ahead by allowing the slender XL-23 to deliver an extremely smooth response with constant directivity.

Offering more than just a signature sound, the XL-23 also has a signature style. Its beautifully crafted aluminum extruded enclosure, featuring an anodized black-grain finish and high-gloss black accents, is the direct result of our engineers' quest for perfect balance. In fact, it's a look that brings a splash of sophistication to any room.

For increased placement flexibility, the XL-23 can be paired with the company's optional XFS floor stand.

The entire ICON Series is performance art at its best, capturing the spirit of our past and pushing us into the future. It is a brilliant representation of how our products have evolved and remained desirable over time. After just one listen, the ICON sound will be imprinted in your consciousness forever.

- Patent-pending XT[™] Tractrix[®] Horn technology
- Titanium compression driver creates precise high frequencies
- Dual high-output woofers generate hard-hitting intensity
- Mounts to optional XFS floor stand for increased placement flexibility

SPECIFICATIONS

frequency response	86Hz-23kHz +/-3dB
low frequency extension	64Hz
power handling	70W continuous / 275W peak
recommended amplifier power	125W
sensitivity	94dB @ 2.83V / 1m
nominal impedance	8 ohms compatible
high frequency drivers	0.75" (1.9cm) Titanium diaphragm compression driver mated to 80° x 80° round XT Tractrix [®] Horn
high freq crossover	2500Hz
low frequency drivers	Dual 4" (10.2cm) high-output, fiberglass cone woofers
enclosure material	Aluminum
enclosure type	Bass-reflex via dual front-firing ports
height	26.3" (66.7cm) including removable table stand
width	5.75" (14.6cm)
depth	6.75" (17.1cm) not including removable 8" (20.3cm) diameter table stand
mounting	Wall mount bracket and center channel accessories included (Also fits optional XFS floor stand)
weight	18lbs (8.2kg)
finishes	Black anodized w/ high-gloss Black accents
built from	2007

www.klipsch.com
1-800-KLIPSCH

All specifications are subject to change without notice. ©2007

